

PRECIPITATION MEASURING TECHNOLOGY

Wind Transmitter compact

Part number: 4.3519.00.x00

Measuring transmitter for the measurement of the horizontal wind velocity with frequency output (active signal). Suitable for data loggers.

The cup-star consists of plastic, the housing is made of anodised aluminium and plastic.

The instrument has a threaded pin PG 21 with 2 nuts for mounting.



Specification

Part number: 4.3519.00.x00

Wind speed

Measuring range	0.5 ... 50 m/s
Resolution	0.1 m/s
Accuracy	±3 % of meas. value or ± 0.5 m/s

Data output digital

Frequency	2 Hz ... 630 Hz
-----------	-----------------

Operating voltage

Electronic	3.3 V ... 42 V DC
Current consumption	1 mA
Heating	24 V AC/DC, max 20 W

General

Ambient temp.	-40 ... +70 °C
Protection	IP 55

Versions

As per 4.3519.00.x00, but:

Product number 4.3619.00.000

Operating voltage

Heating	24 V AC/DC, max 20 W
---------	----------------------

General

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm ²
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

Product number 4.3519.00.700

General


Electr. connection	7- pole plug
Dimension	Ø 135 x 225 mm
Weight	0.4 kg

Product number 4.3519.00.000

General

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm ²
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

Accessories

Product	Product name	Brief description
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter.
		General
		Material Aluminium



Traverse for Wind Transmitters Compact
4.3171.3x.000

For mounting the wind transmitter and wind direction transmitter jointly onto a mast.

Material	
Traverse	aluminium (AlMgSi0.5)
Gripping clamb	stainless steel
General	
Sensor distance horizontal	0.8 m
Weight	0.35 kg
Mounting	hole Ø 29 mm



Traverse short for Wind Transmitters Compact
4.3171.4x.000

For mounting one wind transmitter or wind direction transmitter at a mast.

Material	
Traverse	aluminium (AlMgSi0.5)
Gripping clamb	stainless steel
General	
Sensor distance horizontal	0.4 m
Weight	0.3 kg
Mounting	hole Ø 29 mm



Holder compact
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

General	
Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Mounting	hole Ø 32.5 mm