

Wind Direction Transmitter Compact

Part number: 4.3129.60.x01

Measuring transmitter for the measurement of the horizontal wind direction with serial output signal. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.

The instrument has a threaded pin PG 21 with 2 nuts for mounting.



Specification

Part number: 4.3129.60.x01

Wind direction

Measuring range	0 ... 360 °
Resolution	0.35 °
Accuracy	±1 °

Data output digital

Output type	10-bit serial synchron
-------------	------------------------

Operating voltage

Electronic	3.3 ... 30 V DC
Current consumption	1 mA
Heating	24 V AC/DC, max 20 W

General

Ambient temp.	-50 ... +70 °C
Protection	IP 55

Versions

As per 4.3129.60.x01, but:

Product number 4.3129.60.701

General



Electr. connection	7 - pol plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.60.001

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Accessories

Product	Product name	Brief description										
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter. General <table border="1"> <tr> <td>Material</td> <td>Aluminium</td> </tr> </table>	Material	Aluminium								
Material	Aluminium											
	Traverse for Wind Transmitters Compact 4.3171.3x.000	For mounting the wind transmitter and wind direction transmitter jointly onto a mast. Material <table border="1"> <tr> <td>Traverse</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Gripping clamb</td> <td>stainless steel</td> </tr> </table> General <table border="1"> <tr> <td>Sensor distance horizontal</td> <td>0.8 m</td> </tr> <tr> <td>Weight</td> <td>0.35 kg</td> </tr> <tr> <td>Mounting</td> <td>hole Ø 29 mm</td> </tr> </table>	Traverse	aluminium (AlMgSi0.5)	Gripping clamb	stainless steel	Sensor distance horizontal	0.8 m	Weight	0.35 kg	Mounting	hole Ø 29 mm
Traverse	aluminium (AlMgSi0.5)											
Gripping clamb	stainless steel											
Sensor distance horizontal	0.8 m											
Weight	0.35 kg											
Mounting	hole Ø 29 mm											



Traverse short for
Wind Transmitters
Compact
4.3171.4x.000

For mounting one wind transmitter or wind direction transmitter at a mast.

Material	
Traverse	aluminium (AlMgSi0.5)
Gripping clamb	stainless steel
General	
Sensor distance horizontal	0.4 m
Weight	0.3 kg
Mounting	hole Ø 29 mm



Geovane
4.3190.00.900

The product set combines the precise wind vanes from Thies CLIMA with the advanced Geovane from Kintech Engineering. The Geovane uses GPS and the sun position to automatically determine the exact north direction 1° accurate. This combination ensures the highest accuracy of wind direction against the geographic north point as a reference.

- Geovane for automatic north correction
- 1° precise wind vanes from Thies CLIMA
- Wind vane and geovane are preconfigured
- Ideal e.g. for site surveys, power curve monitoring and meteorology

Wind direction	
Measuring range	0 ... 380 °
Resolution	0.06° RS-485 0.11° Analog voltage outputs 0.06... 0.16° Frequency output
Accuracy	1°
Miscellaneous	
Electrical input	0 ... 30 V
Operating voltage	
Electronic	6 ... 12 V DC
General	
Ambient temp.	-25 ... +85 °C
Mounting	Onto mast tube Ø34mm
Protection	IP 67
Measuring time	1, 5, 10, 30, 60 seconds
Weight	0,815 kg



Holder compact
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

General

Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Mounting	hole Ø 32.5 mm