

## WIND MEASURING TECHNOLOGY

### Wind Transmitter compact

**Part number: 4.3619.00.xxx**

Measuring transmitter for the measurement of the horizontal wind velocity with analog output. Suitable for data loggers.

The cup-star consists of plastic, the housing is made of anodised aluminium and plastic. The instrument has a threaded pin PG 21 with 2 nuts for mounting.



## Specification

**Part number: 4.3619.00.xxx**

### Wind speed

Measuring range	see model
Resolution	0.1 m/s
Accuracy	±3 % of meas. value or ± 0.5 m/s

### Operating voltage

Current consumption	50 mA
Heating	24 V AC/DC, max 20 W

### General

Ambient temp.	-40 ... +70 °C
Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Protection	IP 55

## Versions

As per 4.3619.00.xxx, but:

**Product number 4.3619.00.140**

### Wind speed

Measuring range	0.5 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 20 mA
Stromausgang	max. 500 ê

**Operating voltage**

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

**General**

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

**Product number 4.3619.00.141**
**Wind speed**

Measuring range	0.5 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	4 ... 20 mA
Stromausgang	max. 500 ê

**Operating voltage**

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

**General**

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

**Product number 4.3619.00.161**
**Wind speed**

Measuring range	0.5 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 10 V
Stromausgang	min. 1 kê

**Operating voltage**

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

**General**

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

**Product number 4.3619.00.167**
**Wind speed**

Measuring range	0.5 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 2 V
Stromausgang	min. 1 k $\hat{e}$

**Operating voltage**

Electronic	9 ... 30 V DC or 24 V AC
------------	-----------------------------

**General**

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

**Product number 4.3619.00.173**
**Wind speed**

Measuring range	0.5 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 5 V
Stromausgang	min. 1 k $\hat{e}$

**Operating voltage**

Electronic	9 ... 30 V DC or 24 V AC
------------	-----------------------------

**General**

Electr. connection	12 m cable, LiyCY 5 x 0.25 mm <sup>2</sup>
Dimension	Ø 135 x 165 mm
Weight	0.75 kg

**Product number 4.3619.00.740**

---

**Wind speed**

Measuring range	0 ... 60 m/s
-----------------	--------------

**Data output analog**

Wind speed	0 ... 20 mA
------------	-------------

Stromausgang	max. 500 ê
--------------	------------

**Operating voltage**

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

**General**

Electr. connection	7- pole plug
--------------------	--------------

Dimension	Ø 135 x 225 mm
-----------	----------------

Weight	0.4 kg
--------	--------

---

**Product number 4.3619.00.741**
**Wind speed**

Measuring range	0 ... 60 m/s
-----------------	--------------

**Data output analog**

Wind speed	4 ... 20 mA
------------	-------------

Stromausgang	max. 500
--------------	----------

**Operating voltage**

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

**General**

Electr. connection	7- pole plug
--------------------	--------------

Dimension	Ø 135 x 225 mm
-----------	----------------

Weight	0.4 kg
--------	--------

---

**Product number 4.3619.00.761**
**Wind speed**

Measuring range	0 ... 60 m/s
-----------------	--------------

**Data output analog**

Wind speed	0 ... 10 V
------------	------------

Stromausgang	min. 1 k
--------------	----------

**Operating voltage**





---

Electronic	13 ... 30 V DC or 24 V AC
------------	------------------------------

### General

Electr. connection	7- pole plug
Dimension	Ø 135 x 225 mm
Weight	0.4 kg

## Accessories

Product	Product name	Brief description										
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter.  <b>General</b> <table border="1"> <tr> <td>Material</td> <td>Aluminium</td> </tr> </table>	Material	Aluminium								
Material	Aluminium											
	Traverse for Wind Transmitters Compact 4.3171.3x.000	For mounting the wind transmitter and wind direction transmitter jointly onto a mast.  <b>Material</b> <table border="1"> <tr> <td>Traverse</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Gripping clamb</td> <td>stainless steel</td> </tr> </table> <b>General</b> <table border="1"> <tr> <td>Sensor distance horizontal</td> <td>0.8 m</td> </tr> <tr> <td>Weight</td> <td>0.35 kg</td> </tr> <tr> <td>Mounting</td> <td>hole Ø 29 mm</td> </tr> </table>	Traverse	aluminium (AlMgSi0.5)	Gripping clamb	stainless steel	Sensor distance horizontal	0.8 m	Weight	0.35 kg	Mounting	hole Ø 29 mm
Traverse	aluminium (AlMgSi0.5)											
Gripping clamb	stainless steel											
Sensor distance horizontal	0.8 m											
Weight	0.35 kg											
Mounting	hole Ø 29 mm											
	Traverse short for Wind Transmitters Compact 4.3171.4x.000	For mounting one wind transmitter or wind direction transmitter at a mast.  <b>Material</b> <table border="1"> <tr> <td>Traverse</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Gripping clamb</td> <td>stainless steel</td> </tr> </table> <b>General</b> <table border="1"> <tr> <td>Sensor distance horizontal</td> <td>0.4 m</td> </tr> <tr> <td>Weight</td> <td>0.3 kg</td> </tr> <tr> <td>Mounting</td> <td>hole Ø 29 mm</td> </tr> </table>	Traverse	aluminium (AlMgSi0.5)	Gripping clamb	stainless steel	Sensor distance horizontal	0.4 m	Weight	0.3 kg	Mounting	hole Ø 29 mm
Traverse	aluminium (AlMgSi0.5)											
Gripping clamb	stainless steel											
Sensor distance horizontal	0.4 m											
Weight	0.3 kg											
Mounting	hole Ø 29 mm											



Holder compact  
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

**General**

Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Mounting	hole Ø 32.5 mm